




Drive-through scale

7784, 2814

- ▶ Approvable, class III
- ▶ Robust steel structure
- ▶ Low drive-on height
- ▶ Measurement cable: 6m
- ▶ Can be combined with all approvable Soehnle Professional terminals





Features

- ▶ Approvable, class III
- ▶ Robust steel structure
- ▶ Low drive-on height (max 50 mm)
- ▶ Load-capacity: 1.500 kg
- ▶ Drive-on ramps for easy drive-on with load, length: 500 mm (optional)
- ▶ Measurement cable: 6m (other cable lengths on request)
- ▶ Stainless steel configuration: Weighing platform made from 1.4301 stainless steel, glassbead-blasted, load cell made from stainless steel, protection class IP 68
- ▶ Painted configuration: load cell: nickel-plated steel, protection class IP 67
- ▶ Terminal box protection class IP 65 (protection class can be increased to IP 68 with potted terminal box, see accessories)
- ▶ Foot plates for fixing the scale / ramps included
- ▶ Optionally with plug-in connection to the terminal
- ▶ Can be combined with all approvable Soehnle Professional terminals
- ▶ Order no. 7784 with terminal 3025 (alphanumeric keyboard), incl. wall bracket and 1 piece drive-on ramp 2505.03.00x

Products

Order number Variation	Approvable	Division g	Maximum load kg	Model	Platform size mm
7784.01.002 Drive-through scale	Yes	100 200	300 600	Stainless steel, Terminal 3025	1000 x 800 x 40
7784.02.001 Drive-through scale	Yes	100 200	300 600	Stainless steel, Terminal 3025	1000 x 800 x 40
7784.11.001 Drive-through scale	Yes	100 200	300 600	Painted, Terminal 3025	1000 x 800 x 40
7784.12.001 Drive-through scale	Yes	200 500	600 1500	Painted, Terminal 3025	1500 x 1250 x 50
2814.01.002 Drive-through scale	Yes	100 200	300 600	Stainless steel	1000 x 800 x 40
2814.02.002 Drive-through scale	Yes	200 500	600 1500	Stainless steel	1500 x 1250 x 50
2814.11.002 Drive-through scale	Yes	100 200	300 600	Painted	1000 x 800 x 40
2814.12.002 Drive-through scale	Yes	200 500	600 1500	Painted	1500 x 1250 x 50

Accessories

Order number Variation		Description
2505.03.005		Drive-on ramp smooth, 1000 x 500 x 40 mm, for platform 1,000 x 800 mm stainless steel configuration
2505.03.006		Drive-on ramp smooth, 1,450 x 500 x 50 mm, for platform 1,500 x 1,250 mm stainless steel configuration
2505.03.007		Drive-on ramp smooth, 1000 x 500 x 40 mm, for platform 1,000 x 800 mm painted configuration
2505.03.008		Drive-on ramp smooth, 1,450 x 500 x 50 mm, for platform 1,500 x 1,250 mm painted configuration
2516.01.005		Terminal box in protection class IP 68, potted
2540.01.005		ATEX zone 2/22 configuration for weighing platforms 2814.01.002, 2814.02.002
2540.01.006		ATEX zone 2/22 configuration for weighing platforms 2814.11.002, 2814.12.002